ABLE COI LOW GLARE LED PANEL PLCA-6030-PA-COI





- Cyanosis COI<3.3 low glare back-lit power adjustable LED panel.
- Remote flicker free driver with dimming & control options available.
- 100% PMMA LGP to prevent yellowing.

Product Information

Part Number

Total Weight

raitivullibei	FLCA-0030-FA-COI
Delivered Lumens +/-5%	3600lm 40W
Power	26-40W adjustable
UGR	<19
IP Rating	IP54 front
IK Rating	n/a
IC rating	n/a
Warranty	3 Years
LED Tune	SMD
LED Type	******
ССТ	3/4/5K CCT select
CRI	90
Beam Angle	110°
Colour Stability (SDCM)	3 step Macadam Ellipse
Led Rated Lifetime L70 @25°	>50000hrs
Driver	Remote
Mains Supply	220-240V, 50/60Hz
Driver output Voltage	DC23-40V
Power Factor	0.09
LED Current (nominal)	600mA
Operating Temperature	0-40°C
Body Material	Aluminium
Diffuser Material	Opalised PMMA
Product Finish	Powder coated
Colours	White

2.75kg

PLCA-6030-PA-COI

Dimensions



PLVRK6030 - Recessed mount kit



IP50 back, 26mm deep

