ABLE LOW GLARE LED PANEL PLCA-1230-PA





- Low glare back-lit power adjustable LED panel.
- Remote flicker free driver with dimming & control options available.
- 100% PMMA LGP to prevent yellowing.

Product Information

Dart Number

Dimensions

Part Number	PLV-12030-PA	
Delivered Lumens +/-5%	4800lm 40W	
Power	26-40W adjustable	295mm
UGR	<19	
IP Rating	IP40	
IK Rating	n/a	
IC rating	n/a	
Warranty	3 Years	
LED Type	SMD	
сст	3/4/5/6.5K CCT select	
CRI	80, 90	
Beam Angle	110°	
Colour Stability (SDCM)	3 step Macadam Ellipse	
Led Rated Lifetime L70 @25°	>50000hrs	
Driver	Remote	
Mains Supply	220-240V, 50/60Hz	
Driver output Voltage	DC23-40V	
Power Factor	0.09	
LED Current (nominal)	600mA	
Operating Temperature	0-40°C	
Body Material	Aluminium	
Diffuser Material	Opalised PMMA	
Product Finish	Powder coated	
Colours	White	
Total Weight	3.2kg	

DIV 12020 DA



PLVRK12030 - Recessed mount kit



IP50 back, 26mm deep

