



- Tough IP65 IK10 LED Bunker light.
- Integral driver with dimming & control options available.
- Matching non emergency version in range

Product Information

Part Number

Operating Temperature

Body Material

Product Finish

Total Weight

Colours

Diffuser Material

T di ci valimoni	DITCOODEN
Delivered Lumens +/-5%	2420lm
Power	20W
UGR	n/a
IP Rating	IP65
IK Rating	IK10
IC rating	n/a
Warranty	3 Years
LED Type	SMD
ССТ	3/4К
CRI	80
Beam Angle	110°
Colour Stability (SDCM)	5 step Macadam Ellipse
Led Rated Lifetime L70 @25°	>50000hrs
Driver	Integral
Mains Supply	220-240V, 50/60Hz
Driver output Voltage	DC36V
Power Factor	0.09
LED Current (nominal)	500mA

0-40°C

Aluminium


Black, Grey

2.53kg


Polycarbonate

Powder coated

BHC360EM



Dimensions



Operating mode	Maintained
Battery	NiCd

Luminaire									
Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m
C0 - D25	11.5	13.2	14.8	15.7	16.1	16.4	16.8	17.3	17.6
C90 - D25	11.5	13.2	14.8	15.7	16.1	16.4	16.8	17.3	17.6

Sensor options	BHC360-MS motion sensor on/off
	BHC360-SD step dim 100/20%