



- Low glare deep reflector COB downlight.
- Remote flicker free driver with dimming & control options available.
- Reflector available in either matt or specular finish.


Product Information

| Part Number | DLB280-50W |
|-----------------------------|------------------------|
| Delivered Lumens +/-5% | 5130lm |
| Power | 50W |
| UGR | <17 |
| IP Rating | IP44 front face |
| IK Rating | n/a |
| IC rating | n/a |
| Warranty | 3 Years |
| | |
| LED Type | СОВ |
| ССТ | 2.7/3/4/5K/6K CCT |
| CRI | 90 |
| Beam Angle | 25°, 32° and 40° |
| Colour Stability (SDCM) | 3 step Macadam Ellipse |
| Led Rated Lifetime L70 @25° | >50000hrs |
| | |
| Driver | Remote |

| Driver | Remote |
|-----------------------|-------------------|
| Mains Supply | 220-240V, 50/60Hz |
| Driver output Voltage | DC40V |
| Power Factor | 0.09 |
| LED Current (nominal) | 1200mA |
| Operating Temperature | 0-40°C |
| | |

| Body Material | Aluminium |
|-------------------|---------------|
| Diffuser Material | Polycarbonate |
| Product Finish | Powder coated |
| Colours | White, Black |
| Total Weight | 1.11kg |

Dimensions



Cutout 240mm

Size range from 170-280mm diameter





dck Yf WUZhWca 'Ui