



- Low glare deep reflector COB downlight.
- Remote flicker free driver with dimming & control • options available.
- Reflector available in either matt or specular finish. •

## **Product Information**


## Dimensions

Part Number	DLB280-70W
Delivered Lumens +/-5%	6820lm
Power	70W
UGR	<17
IP Rating	IP44 front face
IK Rating	n/a
IC rating	n/a
Warranty	3 Years
LED Type	СОВ
ССТ	2.7/3/4/5K/6K CCT
CRI	90
Beam Angle	25°, 32° and 40°
Colour Stability (SDCM)	3 step Macadam Ellipse
Led Rated Lifetime L70 @25°	>50000hrs
Driver	Remote
Mains Supply	220-240V, 50/60Hz
Driver output Voltage	DC50V
Devues Feetes	0.00

Driver	Remote
Mains Supply	220-240V, 50/60Hz
Driver output Voltage	DC50V
Power Factor	0.09

Power Factor	0.09
LED Current (nominal)	1700mA
Operating Temperature	0-40°C

Body Material A	Aluminium
Diffuser Material P	Polycarbonate
Product Finish P	Powder coated
Colours V	White, Black
Total Weight 1	1.12kg



Cutout 240mm

## Size range from 170-280mm diameter





## dck Yf WUZhWca 'Ui