



- Dome top LED IP65 bollard with louvered reflector.
- Integral driver with dimming & control options available
- Range includes flat top, conical reflector & 600mm high fittings.


Product Information

Dimensions

| Part Number | BED15100-20W-DT |
|---|------------------------------|
| Delivered Lumens +/-5% | 1165lm |
| Power | 20W |
| UGR | n/a |
| IP Rating | IP65 |
| IK Rating | IK08 |
| IC rating | n/a |
| Warranty | 3 Years |
| | |
| LED Type | СОВ |
| ССТ | 3/4/6К |
| CRI | 80, 90 |
| Beam Angle | n/a |
| Colour Stability (SDCM) | 5 step Macadam Ellipse |
| Led Rated Lifetime L70 @25° | >50000hrs |
| | |
| Driver | Integral |
| Mains Supply | 220-240V, 50/60Hz |
| Driver output Voltage | DC36V |
| Power Factor | |
| | 0.09 |
| LED Current (nominal) | 0.09 500mA |
| | |
| LED Current (nominal) | 500mA |
| LED Current (nominal) Operating Temperature | 500mA |
| LED Current (nominal) | 500mA 0-40°C |
| LED Current (nominal) Operating Temperature Body Material | 500mA 0-40°C Aluminium |

Black, Grey

5.49kg





Colours

Total Weight