



- Open face IP65 surface mount downlight with deep faceted lens for visual comfort.
- Integral flicker free driver with dimming & control options available.
- Complete range of sizes & complementary wall mount fittings available.

Product Information

Part Number	SMED0812-OF-10W
Delivered Lumens +/-5%	1112lm
Power	10W
UGR	n/a
IP Rating	IP65
IK Rating	IK08
IC rating	n/a
Warranty	3 Years
LED Type	СОВ
ССТ	3/4/6K
CRI	80, 90
Beam Angle	12°, 24°, 36° and 60°
Colour Stability (SDCM)	5 step Macadam Ellipse
Led Rated Lifetime L70 @25°	>50000hrs
Driver	Integral
Mains Supply	
mains supply	220-240V, 50/60Hz
Driver output Voltage	220-240V, 50/60Hz DC36V
Driver output Voltage	DC36V
Driver output Voltage Power Factor	DC36V 0.09
Driver output Voltage Power Factor LED Current (nominal)	DC36V 0.09 250mA
Driver output Voltage Power Factor LED Current (nominal)	DC36V 0.09 250mA
Driver output Voltage Power Factor LED Current (nominal) Operating Temperature	DC36V 0.09 250mA 0-40°C
Driver output Voltage Power Factor LED Current (nominal) Operating Temperature Body Material	DC36V 0.09 250mA 0-40°C
Driver output Voltage Power Factor LED Current (nominal) Operating Temperature Body Material Diffuser Material	DC36V 0.09 250mA 0-40°C Aluminium 3mm toughened glass
Driver output Voltage Power Factor LED Current (nominal) Operating Temperature Body Material Diffuser Material Product Finish	DC36V 0.09 250mA 0-40°C Aluminium 3mm toughened glass Powder coated

Dimensions



