



- Robust IP65 surface mount down light with 8mm toughened glass lens.
- Integral flicker free driver with dimming & control options available.
- Complete range of sizes & complementary wall mount fittings available.

## **Product Information**

| Part Number                 | SMED1020-10W           |
|-----------------------------|------------------------|
| Delivered Lumens +/-5%      | 895lm                  |
| Power                       | 10W                    |
| UGR                         | n/a                    |
| IP Rating                   | IP65                   |
| IK Rating                   | IK08                   |
| IC rating                   | n/a                    |
| Warranty                    | 3 Years                |
|                             |                        |
| LED Type                    | СОВ                    |
| ССТ                         | 3/4/6K                 |
| CRI                         | 80, 90                 |
| Beam Angle                  | 12°, 24°, 36° and 60°  |
| Colour Stability (SDCM)     | 5 step Macadam Ellipse |
| Led Rated Lifetime L70 @25° | >50000hrs              |
|                             |                        |
| Driver                      | Integral               |
| Mains Supply                | 220-240V, 50/60Hz      |
| Driver output Voltage       | DC36V                  |
| Power Factor                | 0.09                   |
| LED Current (nominal)       | 250mA                  |
| Operating Temperature       | 0-40°C                 |
|                             |                        |
| Body Material               | Aluminium              |
| Diffuser Material           | 8mm toughened glass    |
| Product Finish              | Powder coated          |
| Colours                     | White, Black, Grey     |
| Total Weight                | 1.07kg                 |
|                             | -                      |

## **Dimensions**



