



- Robust IP65 surface mount down light with 8mm toughened glass lens.
- Integral flicker free driver with dimming & control options available.
- Complete range of sizes & complementary wall mount fittings available.

## **Product Information**

Part Number	SMED1515-30W
Delivered Lumens +/-5%	3058lm
Power	30W
UGR	n/a
IP Rating	IP65
IK Rating	IK08
IC rating	n/a
Warranty	3 Years
LED Type	СОВ
ССТ	3/4/6K
CRI	80, 90
Beam Angle	12°, 24°, 36° and 60°
Colour Stability (SDCM)	5 step Macadam Ellipse
Led Rated Lifetime L70 @25°	>50000hrs
Driver	Integral
Driver Mains Supply	Integral 220-240V, 50/60Hz
	<u> </u>
Mains Supply	220-240V, 50/60Hz
Mains Supply Driver output Voltage	220-240V, 50/60Hz DC36V
Mains Supply Driver output Voltage Power Factor	220-240V, 50/60Hz DC36V 0.09
Mains Supply Driver output Voltage Power Factor LED Current (nominal)	220-240V, 50/60Hz DC36V 0.09 750mA
Mains Supply Driver output Voltage Power Factor LED Current (nominal)	220-240V, 50/60Hz DC36V 0.09 750mA
Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature	220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C
Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature  Body Material	220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C
Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature  Body Material Diffuser Material	220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C  Aluminium 8mm toughened glass

## **Dimensions**



