



- Robust IP65 surface mount up/down wall light with 8mm toughened glass lens.
- Integral flicker free driver with dimming & control options available.
- Complete range of sizes & complementary surface mount down lights available.

## **Product Information**

Part Number	WLED1515-2-15W
Delivered Lumens +/-5%	3053lm
Power	2x15W
UGR	n/a
IP Rating	IP65
IK Rating	IK08
IC rating	n/a
Warranty	3 Years
LED Type	СОВ
ССТ	3/4/6K
CRI	80, 90
Beam Angle	12°, 24°, 36° and 60°
Colour Stability (SDCM)	5 step Macadam Ellipse
Led Rated Lifetime L70 @25°	>50000hrs
Led Rated Lifetime L70 @25°	>50000hrs
Led Rated Lifetime L70 @25°  Driver	>50000hrs Integral
Driver	Integral
Driver Mains Supply	Integral 220-240V, 50/60Hz
Driver Mains Supply Driver output Voltage	Integral 220-240V, 50/60Hz DC36V
Driver Mains Supply Driver output Voltage Power Factor	Integral 220-240V, 50/60Hz DC36V 0.09
Driver Mains Supply Driver output Voltage Power Factor LED Current (nominal)	Integral 220-240V, 50/60Hz DC36V 0.09 750mA
Driver Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature	Integral 220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C
Driver Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature  Body Material	Integral 220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C Aluminium
Driver Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature  Body Material Diffuser Material	Integral 220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C  Aluminium 8mm toughened glass
Driver Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature  Body Material Diffuser Material Product Finish	Integral 220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C  Aluminium 8mm toughened glass Powder coated
Driver Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature  Body Material Diffuser Material	Integral 220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C  Aluminium 8mm toughened glass

## **Dimensions**



