



- High efficiency LED high bay, CCT select & power tunable.
- Integral driver with dimming & control options available.
- Variety of reflectors available for different beam angles.

Product Information

Part Number	HBA200
Delivered Lumens +/-5%	30000lm
Power	200W
UGR	<25
IP Rating	IP65
IK Rating	IK08
IC rating	n/a
Warranty	3 Years
LED Type	SMD
LED Type	SMD 3/4/5/6 5K CCT select
ССТ	3/4/5/6.5K CCT select
CCT CRI	3/4/5/6.5K CCT select 80
CCT CRI Beam Angle	3/4/5/6.5K CCT select 80 60°, 90° and 120°
CCT CRI	3/4/5/6.5K CCT select 80
CCT CRI Beam Angle	3/4/5/6.5K CCT select 80 60°, 90° and 120°
CCT CRI Beam Angle Colour Stability (SDCM)	3/4/5/6.5K CCT select 80 60°, 90° and 120° 5 step Macadam Ellipse
CCT CRI Beam Angle Colour Stability (SDCM)	3/4/5/6.5K CCT select 80 60°, 90° and 120° 5 step Macadam Ellipse
CCT CRI Beam Angle Colour Stability (SDCM) Led Rated Lifetime L70 @25°	3/4/5/6.5K CCT select 80 60°, 90° and 120° 5 step Macadam Ellipse >54000hrs

Mains Supply	220-240V, 50/60Hz
Driver output Voltage	DC48V
Power Factor	0.09
LED Current (nominal)	1150mA
Operating Temperature	0-40°C

Body Material	Aluminium	
Diffuser Material	Glass	
Product Finish	Powder coated	
Colours	Black	
Total Weight	3.8kg	

Dimensions

