

- Wide body commercial LED batten.
- Integral driver with dimming & control options.
- Large PA16 terminal block.
- Motion sensor options available.


Product Information

Part Number	BLB40-1200
Delivered Lumens +/-5%	4237lm
Power	40W
UGR	<19
IP Rating	IP20
IK Rating	n/a
IC rating	n/a
Warranty	3 Years
LED Type	SMD
ССТ	4K
CRI	80
Beam Angle	110°
Colour Stability (SDCM)	5 step Macadam Ellipse
Colour Stability (SDCM) Led Rated Lifetime L70 @25°	5 step Macadam Ellipse >50000hrs
Led Rated Lifetime L70 @25°	>50000hrs
Led Rated Lifetime L70 @25° Driver	>50000hrs Integral
Led Rated Lifetime L70 @25° Driver Mains Supply	>50000hrs Integral 220-240V, 50/60Hz
Led Rated Lifetime L70 @25° Driver Mains Supply Driver output Voltage	>50000hrs Integral 220-240V, 50/60Hz DC36V
Led Rated Lifetime L70 @25° Driver Mains Supply Driver output Voltage Power Factor	>50000hrs Integral 220-240V, 50/60Hz DC36V 0.09
Led Rated Lifetime L70 @25° Driver Mains Supply Driver output Voltage Power Factor LED Current (nominal)	>50000hrs Integral 220-240V, 50/60Hz DC36V 0.09 750mA
Led Rated Lifetime L70 @25° Driver Mains Supply Driver output Voltage Power Factor	>50000hrs Integral 220-240V, 50/60Hz DC36V 0.09
Led Rated Lifetime L70 @25° Driver Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature	>50000hrs Integral 220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C
Led Rated Lifetime L70 @25° Driver Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature Body Material	>50000hrs Integral 220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C Steel
Led Rated Lifetime L70 @25° Driver Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature	>50000hrs Integral 220-240V, 50/60Hz DC36V 0.09 750mA 0-40°C


White

3.2kg

Dimensions







Sensor options BLB40-1200-MS motion sensor on/off BLB40-1200-SD step dim 100/20%

dck Yf WUZhWca 'Ui

Microwave motion sensor MC076S



Colours

Total Weight