




- Cyanosis COI<3.3 low glare edge-lit power adjustable LED panel.
- Remote flicker free driver with dimming & control options available.
- 100% PMMA LGP to prevent yellowing.

Product Information

Part Number	PLV-6060-PA-COI
Delivered Lumens +/-5%	3600lm 40W
Power	26-40W adjustable
UGR	<19
IP Rating	IP54 front
IK Rating	n/a
IC rating	n/a
Warranty	3 Years
LED Type	SMD
ССТ	3/4/5K CCT select
CRI	90
Beam Angle	110°
Colour Stability (SDCM)	3 step Macadam Ellipse
Led Rated Lifetime L70 @25°	>50000hrs
Driver	Remote
Driver Mains Supply	Remote 220-240V, 50/60Hz
Mains Supply	220-240V, 50/60Hz
Mains Supply Driver output Voltage	220-240V, 50/60Hz DC23-40V
Mains Supply Driver output Voltage Power Factor	220-240V, 50/60Hz DC23-40V 0.09
Mains Supply Driver output Voltage Power Factor LED Current (nominal)	220-240V, 50/60Hz DC23-40V 0.09 600mA
Mains Supply Driver output Voltage Power Factor LED Current (nominal)	220-240V, 50/60Hz DC23-40V 0.09 600mA
Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature	220-240V, 50/60Hz DC23-40V 0.09 600mA 0-40°C
Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature Body Material	220-240V, 50/60Hz DC23-40V 0.09 600mA 0-40°C
Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature Body Material Diffuser Material	220-240V, 50/60Hz DC23-40V 0.09 600mA 0-40°C Aluminium Opalised PMMA
Mains Supply Driver output Voltage Power Factor LED Current (nominal) Operating Temperature Body Material Diffuser Material Product Finish	220-240V, 50/60Hz DC23-40V 0.09 600mA 0-40°C Aluminium Opalised PMMA Powder coated

Dimensions



PLVRK6060 - Recessed mount kit



Reinforced concave-convex edge folded backplate

