



- IP65 low glare edge-lit power adjustable LED panel.
- Remote flicker free driver with dimming & control options available.
- 100% PMMA LGP to prevent yellowing.

## **Product Information**

| Part Number                 | PLV-6030-PA-IP65       |
|-----------------------------|------------------------|
| Delivered Lumens +/-5%      | 4800lm 40W             |
| Power                       | 26-40W adjustable      |
| UGR                         | <19                    |
| IP Rating                   | IP65                   |
| IK Rating                   | n/a                    |
| IC rating                   | n/a                    |
| Warranty                    | 3 Years                |
|                             |                        |
| LED Type                    | SMD                    |
| ССТ                         | 3/4/5/6.5K CCT select  |
| CRI                         | 80                     |
| Beam Angle                  | 110°                   |
| Colour Stability (SDCM)     | 3 step Macadam Ellipse |
| Led Rated Lifetime L70 @25° | >50000hrs              |
|                             |                        |
| Driver                      | Remote                 |
| Mains Supply                | 220-240V, 50/60Hz      |
| Driver output Voltage       | DC23-40V               |
| Power Factor                | 0.09                   |
| LED Current (nominal)       | 600mA                  |
| Operating Temperature       | 0-40°C                 |
|                             |                        |
| Body Material               | Aluminium              |
| Diffuser Material           | Opalised PMMA          |
| Product Finish              | Powder coated          |
| Colours                     | White                  |
| Total Weight                | 2.75kg                 |

## **Dimensions**



PLVRK6030 - Recessed mount kit



IP65 rear cable connection

